



# HPI-T High Wattage

## HPI-T 2000W/646 E40 220V CRP/4

Quartz metal halide lamps with clear outer bulb

### Product data

General Information	
Cap-Base	E40 [ E40]
Operating Position	P75 [ Parallel +/-75D or Horizontal(HOR)]
Life To 5% Failures (Nom)	3000 h
Life To 10% Failures (Nom)	5500 h
Life To 20% Failures (Nom)	8000 h
Life To 50% Failures (Nom)	12000 h
System Description	-
Light Technical	
Color Code	646 [ CCT of 4600K]
Luminous Flux (Rated) (Min)	182000 lm
Luminous Flux (Rated) (Nom)	189000 lm
Color Designation	Cool White (CW)
Lumen Maintenance 10000 h (Nom)	60 %
Lumen Maintenance 2000 h (Nom)	77 %
Lumen Maintenance 5000 h (Nom)	67 %
Chromaticity Coordinate X (Nom)	375
Chromaticity Coordinate Y (Nom)	385
Correlated Color Temperature (Nom)	4200 K
Luminous Efficacy (rated) (Nom)	96 lm/W
Color Rendering Index (Nom)	65
Operating and Electrical	
Lamp supply voltage	220 V [ 220]

Power (Rated) (Nom)	1960.0 W
Lamp Current Run-Up (Max)	28.4 A
Lamp Current (EM) (Nom)	16.5 A
Ignition Peak Voltage (Max)	5000 V
Ignition Supply Voltage (Min)	198 V
Ignition Time (Max)	30 s
Voltage (Max)	140 V
Voltage (Min)	120 V
Voltage (Nom)	130 V

Controls and Dimming	
Dimmable	No

Mechanical and Housing	
Bulb Finish	Clear

Approval and Application	
Energy Efficiency Label (EEL)	A+
Mercury (Hg) Content (Nom)	155 mg
Energy Consumption kWh/1000 h	2156 kWh

Luminaire Design Requirements	
Bulb Temperature (Max)	600 °C
Cap-Base Temperature (Max)	300 °C

## HPI-T High Wattage

### Product Data


Full product code	871150018376745
Order product name	HPI-T 2000W/646 E40 220V CRP/4
EAN/UPC - Product	8711500183767
Order code	928073609231
Numerator - Quantity Per Pack	1

Numerator - Packs per outer box	4
Material Nr. (12NC)	928073609231
Net Weight (Piece)	569.000 g
ILCOS Code	MT-2000/46/2B-H-E40-/H

### Warnings and Safety

- Use only in totally enclosed luminaire, even during testing (IEC61167, IEC 62035, IEC60598)
- The luminaire must be able to contain hot lamp parts if the lamp ruptures
- For use with control gear designed for high-pressure mercury lamps
- A lamp breaking is extremely unlikely to have any impact on your health. If a lamp breaks, ventilate the room for 30 minutes and remove the parts, preferably with gloves. Put them in a sealed plastic bag and take it to your local waste facilities for recycling. Do not use a vacuum cleaner.


### Dimensional drawing



HPI-T 2000W/646 E40 220V

Product	D	O	L	C
HPI-T 2000W/646 E40 220V CRP/4	101.5 mm	89 mm	290 mm	430 mm

### Photometric data



HPI-T

## HPI-T High Wattage

