

T.			U_f	I_f	Cl.	f	U_a	U_{g2}	U_{g1}	I_a	I_{g2}	I_{g1}	$U_{g1 \approx}$	P_{dr}	R_o	P_o	P_a					
			V	A		MHz	V	V	V	mA	mA	mA	V	W	kΩ	W	W					
RS 683	T1f	1	5	8	C-Tgr	≤ 100	2000	350	-100	200	50	25	230	5,8	6	275	125					
						≤ 100	2500	350	-150	200	40	25	280	7	7	375	125					
						≤ 100	3000	350	-150	180	30	20	270	5,4	9	400	140					
					C-T1f	≤ 100	2500	350	-210	135	30	8	290	2,3	11	250	88					
						A-Mod	≤ 100	2500	350	-60	20 ÷ 175	40	20	150	4,5	8	300	140				
							B-Tgr	≤ 100	2500	350	-60	20 ÷ 175	40	20	150	4,5	8	300	140			
					stat		1000	350		100												
						stat maximum	100	3000	500													150
					200		2000	500														150

$S = 4 \text{ mA/V}; \mu_{(g2/g1)} = 6,7$
 $P_{g2} = 25 \text{ W}; P_{g1} = 7 \text{ W}$
 $P_{g2} = 25 \text{ W}; P_{g1} = 5 \text{ W}$

$C_{g1/k}$	$C_{a/k}$	$C_{g1/a}$	$C_{g1/k}$	$C_{g1/g2}$	$C_{g2/a}$
pF	pF	pF	pF	pF	pF
3,5	0,05	0,05	2,5	8	3,5

